

16 CHANNEL IP NVR 4K/8MP . H265/H264

KEY FEATURES

- 16 channel IP NVR 4K/8MP
- H.265/H.264
- Live playback 4 ch 1080P or 1 ch 4K/8MP
- Recording: 4K/8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1
- 80 Mbps
- HDMI and VGA (1080P) output
- 2 way audio
- 1 HDD SATA
- RJ45 Gigabit
- 2 USB 2.0
- 12V DC
- Desktop





FEATURES

- 16 ch IP NVR
 - Dual Core processor
 - LINUXembedded O/S
 - H.265/H.264
 - 16 IP camera input
 - VGA (1920x1080) and HDMI (1920x1080) video output
 - 2 way audio: 1 RCA in / 1 RCA out
 - Live display 1 ch 8MP/4K (3840x2160) or 4 ch 1080P (1920x1080)
 - Output division: 1, 4, 8, 9, 16
 - Display resolution: 1080P (1920x1080), SXGA (1280x1024), 720P (1280x720)
 - Recording resolution: 4K/8MP (3840x2160), 6MP (3072x2048), 5MP (2560x1920), 4MP (2560x1440), 3MP (2048x1536), 1080P (1920x1080), 720P (1280x720), etc.
 - Recording speed: 80 Mbps
 - Bitrate: 16 ~20480 Kbps
 - Playback: 4 ch 1080P (max 1ch at 8MP/4K)
 - Motion detection: 22x18 selectable grid, adjustable sensibility at various levels, video loss and masking detection
 - Storage: 1x SATA III (up to 6TB per disc, not included)
 - Network interfaceRJ45 (10/100/1000M)
 - Network protocols: HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP filter, DDNS, IP search (IP Dahua, DVR, NVS, etc.), Easy4ip
 - ONVIFVersión2.4
 - Remote access up to 128users
 - Connection: 2 USB 2.0
 - Local network and Internet server access
 - Independent motion detection configuration by camera
 - Compatible with 3D positioner function (compatible PTZdomes)
 - Software and hardware watchdog
 - Watermark
 - Limit user access to cameras on local/remote mode
 - Masking areas, alarm by video loss andcamera blank
 - Multilanguage screen menu
 - Display, configuration and remote control by TCP/IP with client programm and IE web browser (compatible twith Firefox and Chrome)
 - eMails sended with attached picture on alarm
 - Programmed FTP or alarm sending
 - Display on Simbian, Blackberry, Windows Mobile, iPhone and Android
 - Fixed or dynamic IP mediante Dyndns service, NoIP, DDNS Evolution, etc.
 - Power supply: 12V DC, 2A
 - Consumption: <3W (without discs)
 - Working temperature: -10°C ~ +55°C
 - Storage temperature: -20°C ~ +70°C
 - RH: 0~90%
- Dimensions: 260 x 224,9 x 47,6 mm (desktop)
 - Weight: 800 g (without HDD)